

B-255

Interlock Nitrile glove, 3/4 coated

PRODUCT FEATURES

- Better sweat absorbing
- Excellent grip in dry environment
- Oil resistance
- Durable



POSSIBLE APPLICATIONS



PERFORMANCE REQUIREMENTS

EN ISO 21420	PASS
EN 388	3111X

EN 388



3111X



CAT. II



DETAILS

B-255 is a protective glove made from interlock lining and Nitrile coating from the palm to the knuckle of hand back. *The light-in-weight cotton fabric allows the glove better sweat absorption.* The glove provides excellent grip in a dry environment, has oil resistance, and is durable. This glove is widely used in the chemical extraction and mold casting industry.

PRODUCT DESCRIPTIONS	
Series	Nitrile
Available Size	6-7-8-9-10-11
Liner Material	Cotton
Liner Color Available	White (other options are available upon request)
Coating	Smooth nitrile
Coating Color Available	Yellow
Design	Palm coated till the knuckle of hand back, knit wrist
Thickness	0.7mm on palm
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°C / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water.
Packaging Reference	12 Pairs x 10 Dispensers x 1 Carton 56x27x29cm

SIZE SPECIFICATIONS

Size:	6	7	8	9	10	11
Total Length (+/-5 mm)	225	230	240	250	260	270
Palm Width (+/-3 mm)	90	95	105	115	125	135
Weight (+/-5% gram/pair)	40	43	47	52	58	65

