



# WR-610

Sandy PolyMAX® winter glove, 15-gauge seamless THERMOLITE® /Nylon/Spandex liner, Palm coated

# **PRODUCT FEATURES**

- THERMOLITE® brand fibers
- Cold resistance
- Skin and environment friendly
- Excellent grip in dry and wet environments
- 360° air permeability
- Light in weight
- High dexterity
- DMF free
- Silicone free
- Solvent free
- **Odorless**



# **POSSIBLE APPLICATIONS**











# PERFORMANCE REQUIREMENTS

EN ISO 21420	PASS				
EN 388	4131X				
EN 1186 Food Contact	PASS				
OEKO-TEX Standard 100	PASS				
Silicone Free	PASS				
Odorless	PASS				
THERMOLITE® TAG	YES				

SIQI Science and Technology Co., Ltd.

□ sqg@sqglove.com

SQG Safety Hi-Tech Co., Ltd.

+86-021-58880636



OEKO-TEX®

SHGO 114383 TESTEX **P∈∈** Tested for harmful substances.

2



**EN 388** 

4131X

# **Product Data Sheet**



# **DETAILS**

WR-610 is a protective glove made from 15-gauge THERMOLITE®/Nylon/Spandex and innovated PolyMAX® coating. PolyMAX® is a unique polymer polyurethane coating with the characteristics of skin and environment-friendly, solvent-free, DMF-free, silicone-free, and odorless. Meanwhile, the THERMOLITE® liner helps you stay warm as the temperature drops. WR-610 provides excellent grip in dry and wet environments and resistance to cold. It also offers high dexterity and 360° air permeability. This glove uses widely in the cold working environment.

PRODUCT DESCRIPTIONS					
Series	PolyMAX®				
Available Size	6-7-8-9-10-11-12				
Liner Material	THERMOLITE®/Nylon/Spandex				
Liner Color Available	Orange				
	(other options are available upon request)				
Coating	PPU				
Coating Color Available	Black				
	(other options are available upon request)				
Design	Palm coated, knit wrist				
Thickness	0.9mm on palm				
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water.				
Packaging Reference	12 Pairs x 12 Dispensers x 1 Carton 48x28x29cm				

# **SIZE SPECIFICATIONS**

Size:	6	7	8	9	10	11	12	
Total Length (+/-5 mm)	210	220	230	240	250	260	270	
Palm Width (+/-3 mm)	75	80	88	96	100	102	104	
Weight (+/-5% gram/pair)	25	26	32	37	38	40	42	

SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





