



# **B6-311T**

Anti-cut PU glove, 13-gauge seamless HPPE/Glass/Steel/Polyester/Spandex A6/F liner, Palm coated, Reinforced

## **PRODUCT FEATURES**

- Cut level A6/F protection
- Touch screen
- Excellent grip in all environments
- High dexterity
- Air permeability



### **POSSIBLE APPLICATIONS**









# PERFORMANCE REQUIREMENTS

EN ISO 21420	PASS
EN 388	4X43F
ANSI Cut Resistant	Level A6
OEKO-TEX Standard 100	PASS
Touch Screen	PASS











Tested for harmful substances. www.oeko-tex.com/standard100



SIQI Science and Technology Co., Ltd.









# **Product Data Sheet**



#### **DETAILS**

B6-311T is a protective glove made from 13-gauge seamless HPPE/Glass/Steel/Polyester/ Spandex and Polyurethane coating. Polyurethane coating has the characteristics of silicone-free and light in weight. B6-311T has a steady performance A6/F cut protection that has reached the highest CE cut resistance. Meanwhile, this glove provides excellent grip in all environments. It also offers high dexterity and air permeability. This glove is widely used in general mechanical protection, for example, packaging, cleaning, and electronic assembly.

PRODUCT DESCRIPTION	ONS
Series	PU
Available Size	7-8-9-10-11
Liner Material	HPPE/Steel/Glass/Spandex/Polyester
Liner Color Available	Grey
	(other options are available upon request)
Coating	High grip PU
Coating Color Available	Black, grey
Design	Palm coated, knit wrist, reinforced thumb crotch
Thickness on Palm	1.0mm on palm
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water.
Packaging Reference	12 Pairs x 12 Dispensers x 1 Carton 52x28x34cm

### SIZE SPECIFICATIONS

Size:	7	8	9	10	11
Total Length (+/-5%)	230	240	250	260	270
Palm Width (+/-3 mm)	90	95	105	108	112
Weight (+/-5% gram/pair)	52	59	64	67	70

SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





