



K5-620

Anti-Cut PolyMAX® glove, 18-gauge seamless TekArmor® A5/E liner, Palm coated, Sandy finished

PRODUCT FEATURES

- Cut level A5/E protection
- Skin and environment friendly
- Excellent grip in dry and wet environments
- Touch screen
- Light oil resistance
- 360° air permeability
- Light and thin
- High dexterity
- DMF free
- Silicone free
- Solvent free
- Odorless



POSSIBLE APPLICATIONS















PERFORMANCE REQUIREMENTS

EN ISO 21420	PASS
EN 388	4X42E
ANSI Cut Resistant	Level A5
Touch Screen	PASS
EN 1186 Food Contact	PASS
OEKO-TEX Standard 100	PASS
Silicone Free	PASS
Odorless	PASS





SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





Product Data Sheet



DETAILS

K5-620 is a protective glove made from an 18-gauge TekArmor® liner and innovated PolyMAX® coating with sandy finished . PolyMAX® is a unique polymer polyurethane coating with the characteristics of skin and environment-friendly, solvent-free, DMF-free, silicone-free and odorless. K5-620 ables to keep steady performance A5/E cut protection and screen touching after washing . Meanwhile, this glove provides excellent grip in dry and wet environments and resistance to light oil. It also offers high dexterity and 360° air permeability. This glove is widely used in general mechanic working areas.

PRODUCT DESCRIPTIONS				
Series	PolyMAX [®] , TekArmor [®]			
Available Size	7-8-9-10-11-12			
Liner Material	HPPE/TekArmor®/Nylon/Spandex			
Liner Color Available	Blue			
	(other options are available upon request)			
Coating	PPU			
Coating Color Available	Black (other options are available upon request)			
Design	Palm coated, knit wrist			
Thickness	0.9mm on palm			
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water.			
Packaging Reference	12 Pairs x 6 Dispensers x 1 Carton 38x28x23cm			

SIZE SPECIFICATIONS

Size:	7	8	9	10	11	12
Total Length (+/-5 mm)	220	230	240	250	260	270
Palm Width (+/-3 mm)	75	79	89	94	97	100
Weight (+/-5% gram/pair)	43	48	53	56	60	62

SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





