



K7-682

Anti-Cut PolyMAX® glove, 18-gauge seamless TekArmor® A7/F liner, Palm coated, TPR on the back

PRODUCT FEATURES

- Cut level A7/F protection
- TPR on the back for impact protection
- Skin and environment friendly
- Excellent grip in dry and wet environments
- Touch screen
- Light oil resistance
- 360° air permeability
- Light and thin
- High dexterity
- DMF free
- Silicone free
- Solvent free
- Odorless



POSSIBLE APPLICATIONS















PERFORMANCE REQUIREMENTS

| EN ISO 21420 | PASS |
|-----------------------|----------|
| EN 388 | 4X42FP |
| ANSI Cut Resistant | Level A7 |
| Touch Screen | PASS |
| EN 1186 Food Contact | PASS |
| OEKO-TEX Standard 100 | PASS |
| Silicone Free | PASS |
| Odorless | PASS |
| | |











SIQI Science and Technology Co., Ltd.



+86-021-58880636





Product Data Sheet



DETAILS

K7-682 is a protective glove made from an 18-gauge TekArmor® liner and innovated PolyMAX® coating. PolyMAX® is a unique polymer polyurethane coating with the characteristics of skin and environment-friendly, solvent-free, DMF-free, silicone-free and odorless. K7-682 has a *steady performance A7/F cut protection, impact protection, and screen touching*. Meanwhile, this glove provides excellent grip in dry and wet environments and resistance to light oil. It also offers high dexterity and 360° air permeability. This glove is widely used in general mechanic working areas.

| PRODUCT DESCRIPTIONS | | | | |
|-------------------------|--|--|--|--|
| Series | PolyMAX®, TekArmor® | | | |
| Available Size | 7-8-9-10-11-12 | | | |
| Liner Material | HPPE/TekArmor®/Nylon/Spandex | | | |
| Liner Color Available | Blue | | | |
| | (other options are available upon request) | | | |
| Coating | PPU | | | |
| Coating Color Available | Black | | | |
| Coating Color Available | (other options are available upon request) | | | |
| Design | Palm coated, knit wrist, TPR on the back | | | |
| Thickness | 0.9mm on palm | | | |
| Wash Care | Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water. | | | |
| Packaging Reference | 12 Pairs x 6 Dispensers x 1 Carton 61x41x29cm | | | |

SIZE SPECIFICATIONS

| Size: | 7 | 8 | 9 | 10 | 11 | 12 | |
|--------------------------|-----|-----|-----|-----|-----|-----|--|
| Total Length (+/-5 mm) | 220 | 230 | 240 | 250 | 260 | 270 | |
| Palm Width (+/-3 mm) | 80 | 88 | 96 | 100 | 102 | 104 | |
| Weight (+/-5% gram/pair) | 110 | 114 | 120 | 124 | 130 | 135 | |

SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





