

## Product Data Sheet

## ST-610

Antistatic PolyMAX<sup>®</sup> glove, 18-gauge seamless Nylon/Carbon liner, Palm coated

#### **PRODUCT FEATURES**

- Antistatic (ESD)
- Skin and environment friendly
- Excellent grip in dry and wet environments
- Touch screen
- Light oil resistance
- 360° air permeability
- Light in weight
- High dexterity
- DMF free
- Silicone free
- Solvent free
- Odorless

#### **POSSIBLE APPLICATIONS**







#### **PERFORMANCE REQUIREMENTS**

EN ISO 21420	PASS			
EN 388	3121X			
EN 16350 Electrostatic Properties	PASS			
EN 407 Thermal Protection	X1XXXX			
EN 1186 Food Contact	PASS			
Touch Screen	PASS			
OEKO-TEX Standard 100	PASS			
Silicone Free	PASS			
Odorless	PASS			



#### SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.

🖂 sqg@sqglove.com 🖇 +86-021-58880636

💿 Room 1707-1709, West Building, 2218 Hunan Road, Pudong New Area, Shanghai, 201204



# **Product Data Sheet**



#### DETAILS

ST-610 is a protective glove made from 18-gauge nylon/carbon and innovated antistatic (ESD) PolyMAX<sup>®</sup> coating. PolyMAX<sup>®</sup> is a unique polymer polyurethane coating with the characteristics of skin and environment-friendly, solvent-free, DMF-free, silicone-free and odorless. ST-610 is an antistatic glove with screen touching. Meanwhile, this glove provides excellent grip in dry and wet environments and resistance to light oil. It also offers high dexterity and 360° air permeability. This glove is widely used in general mechanic working areas due to the fact of ambidextrous with wearing convenient, soft, and comfortable.

PRODUCT DESCRIPTIONS				
Series	PolyMAX®			
Available Size	7-8-9-10-11-12			
Liner Material	Nylon/Carbon			
Liner Color Available	Blue			
	(other options are available upon request)			
Coating	PPU			
Coating Color Available	Black (other options are available upon request)			
Design	Palm coated, knit wrist			
Thickness	0.6mm on palm			
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water.			
Packaging Reference	12 Pair x 12 Dispensers x 1 Carton 48x28x27cm			

### SIZE SPECIFICATIONS

Size:	7	8	9	10	11	12	
Total Length (+/-5 mm)	220	230	240	250	260	270	
Palm Width (+/-3 mm)	82	85	90	93	97	100	
Weight (+/-5% gram/pair)	23	26	30	32	34	36	

SQG Safety Hi-Tech Co., Ltd.

SIQI Science and Technology Co., Ltd.



💿 Room 1707-1709, West Building, 2218 Hunan Road, Pudong New Area, Shanghai, 201204