



WR-266

Sandy Nitrile winter glove, 15-gauge seamless Polyester shell with 10gauge seamless Acrylic Terry liner, 3/4 double coated

PRODUCT FEATURES

- Acrylic terry liner for cold resistance
- Excellent grip in all environments
- Oil resistance
- High dexterity
- Breathable
- Durable



POSSIBLE APPLICATIONS











PERFORMANCE REQUIREMENTS

| EN ISO 21420 | PASS |
|------------------------|-------|
| EN 388 | 4131X |
| EN 511 Cold Protection | 02X |







SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.







Product Data Sheet



DETAILS

WR-266 is a protective glove made from 15-gauge Polyester shell with 10-gauge Acrylic Terry and Nitrile double coating from palm to the knuckle of hand back. *Acrylic terry liner keeps the users' hands warm.* WR-266 provides excellent grip in all environments and oil resistance. It also offers high dexterity and is breathable. This glove is widely used in the cold working environment.

| PRODUCT DESCRIPTIONS | | | | |
|-------------------------|--|--|--|--|
| Series | Nitrile | | | |
| Available Size | 7-8-9-10-11 | | | |
| Liner Material | Polyester/Acrylic Terry | | | |
| Liner Color Available | Black | | | |
| | (other options are available upon request) | | | |
| Coating | Sandy nitrile | | | |
| Coating Color Available | Black (other options are available upon request) | | | |
| Design | Double coated from palm to the knuckle of hand back, knit wrist | | | |
| Thickness | 1.9mm on palm | | | |
| Wash Care | Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F). Wash in a 5-10 minutes cycle time. Rinse in cold water. | | | |
| Packaging Reference | 12 Pairs x 10 Dispensers x 1 Carton 60x27x43cm | | | |

SIZE SPECIFICATIONS

| C: | - | 0 | 0 | 4.0 | 4.4 |
|--------------------------|-----|-----|-----|-----|-----|
| Size: | / | 8 | 9 | 10 | 11 |
| Total Length (+/-5 mm) | 240 | 250 | 260 | 270 | 280 |
| Palm Width (+/-3 mm) | 100 | 108 | 110 | 117 | 123 |
| Weight (+/-5% gram/pair) | 100 | 110 | 115 | 125 | 135 |

SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.





