



X4-689C

SERIES: X-Plus®

LINER: 21G TekArmor®

COATING: X-Plus® fully coating

WEIGHT: 53g / pair (9')

THICKNESS: liner 0.81mm / palm 1.48mm

SIZE: 6'~12' (SQG size)

FEATURES

Ultra-thin 21G knitting brings flexible and light X-PLUS® is made of Polymer Polyurethane Provides reliable 360° protection Excellent grip in dry, wet and oil condition Touchscreen capability

STANDARDS AND CERTIFICATIONS

EN388: 2016 + A1: 2018 4X42D

ANSI Cut level A4

OEKO-TEK standard 100

Sanitized® antibacterial treatment

Machine washable

Low DMF < 300 ppm

Silicone free

APPLICATION

Glass handing

Sheet metal work

Cutting applications

Bottling

Canning







AVAILABLE

Plastic-free packaging
Bio-based packaging

CARE INSTRUCTIONS

Recommend washing gloves in tempered water not exceeding 104° F or 40° C.A mild commercial laundry soap or detergent should be used.Wash in a 5-10 minute cycle time.Rinse in cold water.Tumbler dry at temperature not exceeding 104° F or 40° C.

Copyright @ 2023 SQG Safety Hi-Tech Co., Ltd. All rights reserved