

EZB6-313R

13G HPPE/RPET/Steel fiber/Glass fiber/Spandex, EZGRIP® palm coating

PRODUCT FEATURES

- Solid ANSI cut level A6/EN388 cut level F
- High level Anti-abrasion with EZGrip® coating
- Reinforcement between the thumb and forefinger
- Outstanding grip in dry and oil condition
- Touchscreen capability



POSSIBLE APPLICATIONS











PERFORMANCE REQUIREMENTS

EN ISO 21420	Pass
EN 388	4X43F
ANSI Cut Resistant	Level A6
OEKO-TEX Standard 100	Pass






















SQG Safety Hi-Tech Co., Ltd. SIQI Science and Technology Co., Ltd.









DETAILS

EZB6-313R is a protective glove made from 13-gauge seamless HPPE/RPET/Steel fiber/Glass fiber/Spandex and PU+NBR coating. The coating has the characteristics of silicone-free and light in weight. The uniqueness of EZB6-313R is that ultra-thin enables users to easily handle tiny objects. Meanwhile, the reinforcement has been added to the web of the thumb for enhanced durability. The glove provides excellent grip in all environments. It also offers high dexterity and air permeability. This glove is widely used in general mechanical protection, for example, packaging, cleaning, and electronic assembly.

PRODUCT DESCRIPTIONS						
Series	EZGRIP®					
Available Size	6-7-8-9-10-11-12					
Liner Material	HPPE,RPET,Steel fiber,Glass fiber,Spandex					
Liner Color Available	Green,Black					
	(other options are available upon request)					
Coating	EZGRIP® plam coating					
Coating Color Available	Black					
Design	Plam coated					
Thickness	0.7mm on palm					
Wash Care	Recommend to use mild detergent or soap and tempered water, avoid using extremely high temperatures when washing and drying (beyond 40°c / 104°F), Wash in a 5-10 minutes cycle time. Rinse in cold water					
Packaging Reference	12 Pairs x 12 Dispensers x 1 Carton 50x28x26cm					

SIZE SPECIFICATIONS

Size:	6	7	8	9	10	11	12
Total Length (+/-8 mm)	220	230	240	250	260	265	275
Palm Width (+/-5 mm)	85	90	95	100	104	107	110
Weight (+/-5% gram/pair)	26	28	32	34	38	40	42



SIQI Science and Technology Co., Ltd.





